Page 1 of 2

# MATERIAL SAFETY DATA SHEET

#### SECTION 1: IDENTIFICATION OF MATERIAL AND SUPPLIER

Product Name: CARBON BUSTER

#### Product Code: CB 20

Use: Automotive Fuel Additive Cleaner

#### Company: ADVANCED AUTOLOGIC Pty Ltd., ACN 008 993 833

Address	PO Box 205 Byford WA, 6122
Telephone No:	(08) 9526 2678
Fax No:	(08) 9526 2680
Emergency No.	(08) 9526 2678 (All Hours)

## SECTION 2: HAZARDS IDENTIFICATION

Hazardous/Non hazardous according to criteria of WorkSafe Australia

Hazard Category F-Flammable

#### 1 1 1011

#### **Risk Phrases**

- R10 Flammable
- R38 Irritating to skin
- R45 May cause sensitisation by skin contact
- **R65** May cause lung damage if swallowed
- R20/21 Harmful by inhalation and in contact with skin

#### **Safety Phrases**

- S2 Keep out of the reach of children
- S20 When using, do not eat or drink
- S25 Avoid contact with eyes

S45 In case of accident or you feel unwell, seek medical advice immediately (show label whenever possible)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## Ingredients

All products are formulated to be non-hazardous to health and environment, wherever possible. All hazardous substances as defined by the NOHSC Code 1008 are listed by CAS No. Other major ingredients that are determined to be non-hazardous are listed without a CAS No.

## Chemical name CAS No. Proportion

Liquid Hydrocarbons	95-47-6	>60%
Proprietary Non-Hazar	<30%	
Ethylene glycol monob	utyl ether 111-76-2	<5%

## **SECTION 4: FIRST AID MEASURES**

#### ACUTE:

SWALLOWED:	Single dose toxicity is low unless there is
	aspiration into lungs where it may cause lung
	damage.
	8
EYE:	Irritation and pain.
SKIN:	May be irritating to the skin. This can result
	in itching and redness of the skin. Poisoning
	may occur from prolonged or massive skin
	contact.
INHALED:	May cause headache and stupour and
	other symptoms of central nervous system
	depression. Mist spray may cause irritation
	of upper respiratory tract.
CHRONIC:	Defats the skin. Prolonged or repeated
	<b>e</b> 1
	contact can cause dermatitis.

#### SECTION 5: FIRE FIGHTING MEASURES

Combustion decomposition products of carbon dioxide and carbon monoxide may be evolved. Use breathing apparatus. Keep containers cool by spraying with water to prevent rupture. Use foam, carbon dioxide or dry chemical fire extinguisher.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Shut off all possible sources of ignition. Remove any naked lights and strong heat sources. DO NOT SMOKE. Absorb with sand or other absorbent material. Dispose at a license landfill. For large spills notify Emergency Services.

## SECTION 7: HANDLING AND STORAGE

Store in a cool, well-ventilated area away from any foodstuffs, oxidising agents and ignition sources.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standards: Not determined.

**Engineering Controls**: Extra ventilation may be required. **Personal Protection**:

Always wash hands before smoking, eating, drinking or using the toilet. Use of barrier cream is recommended. Avoid contact with the skin and breathing in vapours or mist. Follow normal industrial personal protection practises. The use of additional protective clothing depends on the degree and nature of exposure. The following personal protective clothing should be readily available:

- 1. Splash proof chemical safety goggles or face shields
- 2. Neoprene or nitrile rubber gloves
- 3. Chemical resistant rubber boots

4. PVC or leather apron and sleeves or PVC overalls. Details on the use and selection of respiratory protection can be found in Australian Standard AS 1715. Where the concentration of vapour or mist approaches the exposure limit, the following personal protection equipment is recommended

1. For short elevated exposures, use filter respirator with correct organic vapour filter. If the exposure is more than 10 times the exposure limit then the use of an air-supplied respirator may be required.

Flammability: Flammable. Isolate from sources of heat, flame or sparks.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Oil/Amber Coloured LiquidBoiling Point:140-220°CVapour Pressure:Not determinedSpecific Gravity:.92Flashpoint:35 deg CFlammability Limits:Not determinedSolubility in water:Immiscible

# **Other Properties**

pH (1% solution) Not applicable

## SECTION 10: STABILITY AND REACTIVITY

Stable. Keep away from combustibles.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### ACUTE:

SWALLOWED:	Single dose toxicity is low unless there is aspiration into lungs where it may cause lung damage.
EYE:	Irritation and pain.
SKIN:	May be irritating to the skin. This can result in itching and redness of the skin. Poisoning may occur from prolonged or massive skin contact.
INHALED:	May cause headache and stupour and other symptoms of central nervous system depression. Mist spray may cause irritation of upper respiratory tract.
CHRONIC:	Defats the skin. Prolonged or repeated contact can cause dermatitis.

#### SECTION 12: ECOLOGICAL INFORMATION

Do not dispose unused or unwanted product to environment.

#### SECTION 13: DISPOSAL CONSIDERATIONS

Recycle unwanted product or dispose via a waste management contractor.

#### SECTION 14: TRANSPORT INFORMATION

UN Number:	1307
Dangerous Goods Class	3
Subsidiary Risk	Not allocated
Hazchem Code:	3Y
Packing Group:	II
EPG	3A1
Poisons Schedule:	S5

## SECTION 15: REGULATORY INFORMATION

This product is widely used by industry and is not subject to any special regulatory requirements.

## **SECTION 16: OTHER INFORMATION**

This MSDS is valid for five years from date of issue but readers should contact the manufacturer to ensure that this is the latest issue. As per the WorkSafe Guidance Note NOHSC 3017 (Health Risk Assessment) each user should review the information in the specific context of the intended application.

Date of Issue: Formula Code: Contact Point: 07/02/2020 CB 20 Emergency Co-ordinator Mr Michael Croonen (08) 9526 2678