## MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF MATERIAL AND SUPPLIER

Product Name: SUPER SHINE

**Product Code: SS 20** 

Use: Silicone based automotive tyre shine solution

Company: ADVANCED AUTOLOGIC Pty Ltd.,

ACN 008 993 833

Address PO Box 205 Byford WA, 6122

Telephone No: (08) 9526 2678 Fax No: (08) 9526 2680

Emergency No. (08) 9526 2678 (All Hours)

### **SECTION 2: HAZARDS IDENTIFICATION**

Hazardous according to criteria of WorkSafe Australia

**Hazard Category** F - Flammable

**Risk Phrases** 

R11 Highly Flammable

**R24** Toxic in contact with skin

R65 May cause lung damage if swallowed

R48/20 Harmful: danger of serious damage to health by

prolonged exposure through inhalation

**Safety Phrases** 

**S23** Do not breathe vapour

\$24/25 Avoid contact with skin and eyes

**S43** In case of fire use sand, chemical powder or

foam

S62 If swallowed, do not induce vomiting, seek

medical advice immediately and show label.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## **Ingredients**

All products are formulated to be non-hazardous to health and environment, wherever possible. All hazardous sub-stances as defined by the NOHSC Code 1008 are listed by CAS No. Other major ingredients that are determined to be non-hazardous are listed without a CAS No.

# Chemical name CAS No. Proportion

Liquid Hydrocarbons 64742-49-0 >50% Proprietary Non-Hazardous Ingredients <30% Hexane 110-54-3 <20%

## **SECTION 4: FIRST AID MEASURES**

**Swallowed:** If poisoning occurs contact a doctor or

Poisons Information Centre. Phone

13 1126. Do **NOT** induce vomiting. Give plenty of water and seek medical

attention.

**Eye:** Hold eyelids open and immediately flush

with water continuously for 15 minutes.

Seek medical attention.

**Skin:** Remove contaminated clothing and wash

before use. Flush affected area with

plenty of soapy water.

**Inhaled:** Get to fresh air. Unlikely to be a problem.

First Aid Facilities: Eyewash. Deluge shower

Advice to Doctor: Treat symptomatically, similar to

kerosene.

### **SECTION 5: FIRE FIGHTING MEASURES**

Combustion decomposition products of carbon dioxide and carbon monoxide may be evolved. Use breathing apparatus. Keep containers cool by spraying with water to prevent rupture. Use foam, carbon dioxide or dry chemical fire extinguisher.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Shut off all possible sources of ignition. Remove any naked lights and strong heat sources. DO NOT SMOKE. Absorb with sand or other absorbent material. Dispose at a license landfill. For large spills notify Emergency Services.

## **SECTION 7: HANDLING AND STORAGE**

Store in a cool, well-ventilated area, away from any foodstuffs, oxidising agents and ignition sources.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standards: Not determined.

**Engineering Controls**: Extra ventilation is required.

**Personal Protection:** 

Always wash hands before smoking, eating, drinking or using the toilet. Use of barrier cream is recommended. Avoid contact with the skin and breathing in vapours or mist. Follow normal industrial personal protection practises. The use of additional protective clothing depends on the degree and nature of exposure. The following personal protective clothing should be readily available:

- 1. Splash proof chemical safety goggles or face shields
- 2. Neoprene or nitrile rubber gloves
- 3. Chemical resistant rubber boots
- 4. PVC or leather apron and sleeves or PVC overalls. Details on the use and selection of respiratory protection can be found in Australian Standard AS 1715. Where the concentration of vapour or mist approaches the exposure limit, the following personal protection equipment is recommended
- 1. For short elevated exposures, use filter respirator with correct organic vapour filter. If the exposure is more than 10 times the exposure limit then the use of an air-supplied respirator may be required.
- 2. For prolonged, elevated use air supplied respirator or self-contained breathing apparatus (SCBA)

Flammability: Flammable. Isolate from sources

of heat, flame or sparks

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Liquid

Boiling Point: 70-220°C

Vapour Pressure: Not determined

**Specific Gravity:** 0.75 **Flashpoint:** 30°C

Flammability Limits: Not determined

Solubility in Water: Insoluble
Corrosiveness: Non-corrosive
pH (1% solution): Neutral

### **SECTION 10: STABILITY AND REACTIVITY**

Stable. Avoid contact with oxidizers.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## **Health Effects**

**ACUTE:** 

**SWALLOWED:** Single dose toxicity is low unless in the

unlikely event there is aspiration into lungs where it may cause lung damage.

**EYE:** Irritation and pain.

**SKIN:** May be slightly irritating to the skin. This

can result in itching and redness of the skin. Poisoning may occur from prolonged or massive skin contact.

**INHALED:** May cause headache and stupour and

other symptoms of central nervous system depression. Mist Spray may cause irritation of upper respiratory tract.

**CHRONIC:** Defats the skin. Prolonged or repeated

contact can cause dermatitis.

#### **SECTION 12: ECOLOGICAL INFORMATION**

Do not dispose to environment. Refer Section 13.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Recycle unwanted product or dispose via a waste management contractor.

## **SECTION 14: TRANSPORT INFORMATION**

UN Number: 3295 Dangerous Goods Class 3

Subsidiary Risk: None allocated

Hazchem Code: 3[W]E
Packing Group II
EPG 3A1
Poisons Schedule: S5

## **SECTION 15: REGULATORY INFORMATION**

This product is widely used by industry and is not subject to any special regulatory requirements.

#### **SECTION 16: OTHER INFORMATION**

This MSDS is valid for five years from date of issue but readers should contact the manufacturer to ensure that this is the latest issue. As per the WorkSafe Guidance Note NOHSC 3017

(Health Risk Assessment) each user should review the information in the specific context of the intended application.

Date of Issue: 01/08/2019 Formula Code: SS 20

Contact Point: Emergency Co-ordinator

Mr Michael Croonen (08) 9526 2678