# **MATERIAL SAFETY DATA SHEET**

SECTION 1: IDENTIFICATION OF MATERIAL AND SUPPLIER

Product Name: SILICONE LUBE (AEROSOL)

**Product Code: AASL 350G** 

Use: Silicone lubricant

Company: ADVANCED AUTOLOGIC Pty Ltd.,

ACN 008 993 833

Address PO Box 205 Byford WA, 6122

Telephone No: (08) 9526 2678 Fax No: (08) 9526 2680

Emergency No. (08) 9526 2678 (All Hours)

### **SECTION 2: HAZARDS IDENTIFICATION**

Hazardous according to criteria of WorkSafe Australia

### Hazard Category F-Flammable Xn-Harmful

#### **Risk Phrases**

R11 Highly FlammableR38 Irritating to skin

R43 May cause sensitisation by skin contact
 R65 May cause lung damage if swallowed
 R20/21 Harmful by inhalation and in contact with skin

## **Safety Phrases**

**S1/2** Keep locked up and out of the reach of children

Keep container tightly closed.
Keep away from sources of ignition
When using, do not eat or drink
Avoid contact with skin and eyes.

S45 In case of accident or you feel unwell, seek medical advice immediately (show label

whenever possible)

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# **Ingredients**

All products are formulated to be non-hazardous to health and environment, wherever possible. All hazardous sub-stances as defined by the NOHSC Code 1008 are listed by CAS No. Other major ingredients that are determined to be non-hazardous are listed without a CAS No.

# Chemical name CAS No. Proportion

Liquid Hydrocarbons 64742-49-0 <80%
Proprietary Non-Hazardous Ingredients <10%
Carbon Dioxide Propellant To 100%

### **SECTION 4: FIRST AID MEASURES**

**Swallowed:** If poisoning occurs contact a doctor or

Poisons Information Centre. Phone 13 1126. Do **NOT** induce vomiting. Give

plenty of water

**Eye:** Hold eyelids open and immediately flush

with water continuously for 15 minutes.

Seek medical attention.

**Skin:** Remove contaminated clothing and wash

before use. Flush affected area with

plenty of soapy water.

**Inhaled:** Get to fresh air. Unlikely to be a problem.

**First Aid Facilities:** Eyewash. Deluge shower **Advice to Doctor:** Treat symptomatically

# **SECTION 5: FIRE FIGHTING MEASURES**

Combustion decomposition products of carbon dioxide and carbon monoxide may be evolved. Use breathing apparatus. Keep containers cool by spraying with water to prevent rupture. Use foam, carbon dioxide or dry chemical fire extinguisher.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Shut off all possible sources of ignition. Remove any naked lights and strong heat sources. DO NOT SMOKE. Absorb with sand or other absorbent material. Dispose at a license landfill. For large spills notify Emergency Services.

# **SECTION 7: HANDLING AND STORAGE**

Store in a cool, well-ventilated area, away from any foodstuffs, oxidising agents and ignition sources.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Standards**: Not determined.

Engineering Controls: Extra ventilation is required.

**Personal Protection:** 

Always wash hands before smoking, eating, drinking or using the toilet. Use of barrier cream is recommended. Avoid contact with the skin and breathing in vapours or mist. Follow normal industrial personal protection practises. The use of additional protective clothing depends on the degree and nature of exposure. The following personal protective clothing should be readily available:

- 1. Splash proof chemical safety goggles or face shields
- 2. Neoprene or nitrile rubber gloves
- 3. Chemical resistant rubber boots
- 4. PVC or leather apron and sleeves or PVC overalls. Details on the use and selection of respiratory protection can be found in Australian Standard AS 1715. Where the concentration of vapour or mist approaches the exposure limit, the following personal protection equipment is recommended
- 1. For short elevated exposures, use filter respirator with correct organic vapour filter. If the exposure is more than 10 times the exposure limit then the use of an air-supplied respirator may be required.
- 2. For prolonged, elevated use air supplied respirator or self-contained

breathing apparatus (SCBA)

**Flammability:** Flammable. Isolate from sources

of heat, flame or sparks.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Liquid
Boiling Point: Below 100°C
Vapour Pressure: Not determined

Specific Gravity: 0.85 Flashpoint: 12°C

Flammability Limits: Not determined

Solubility in water: miscible pH (1% solution) Neutral

### **SECTION 10: STABILITY AND REACTIVITY**

Stable.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

### **Health Effects**

**ACUTE:** 

SWALLOWED: May cause irritation in stomach. Large

dosage may cause damage to liver or

kidneys

**EYE:** Irritation and pain.

**SKIN:** May be irritating to the skin. This can

result in itching and redness of the skin. Poisoning may occur from prolonged or

massive skin contact.

**INHALED:** May cause headache and stupour and

other symptoms of central nervous system depression. Mist spray may cause irritation of upper respiratory tract.

**CHRONIC:** Defats the skin. Prolonged or repeated

contact can cause dermatitis.

### **SECTION 12: ECOLOGICAL INFORMATION**

Do not dispose to environment. Refer Section 13.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Recycle unwanted product or dispose via a waste management contractor.

### **SECTION 14: TRANSPORT INFORMATION**

UN Number: 1950 Aerosol

Dangerous Goods Class

**Subsidiary Risk** 

Hazchem Code: 2WE
Packing Group: II
EPG 2D1
Poisons Schedule: S6

### **SECTION 15: REGULATORY INFORMATION**

This product is widely used by industry and is not subject to any special regulatory requirements.

# **SECTION 16: OTHER INFORMATION**

This MSDS is valid for five years from date of issue but readers should contact the manufacturer to ensure that this is the latest issue. As per the WorkSafe Guidance Note

**NOHSC 3017** 

(Health Risk Assessment) each user should review the information in the specific context of the intended application.

Date of Issue: 13/02/2020 Formula Code: AASL 350G

Contact Point: Emergency Co-ordinator

Mr Michael Croonen (08) 9526 2678